

Handheld Jammer

IA-01 & IA-02

HiSee-S60J

INTERNATIONAL
ARMOUR
CO.
www.armour.gr



Channel	Frequency Bands MHz	Application	Output Power (Watt)
1	1520-1620	GPS L1 / Galileo E1 / Glonass L1 / BeiDou B1	0.5W
2	1215-1300	GPS L2 / Galileo E6 / Glonass L2 / BeiDou B3	0.5W
3	1300-1400	GPS L3+L4:	0.5W
4	1160-215	GPS L5 / Galileo E5a+E5b/ Glonass L3 / BeiDou B2	0.5W
5	2400-2500	2.4G WiFi /Bluetooth	0.5W
6	1520-1620	GPSL1	0.5W

Handheld jammer IA-02

Channel	Frequency Bands MHz	Application	Output Power (Watt)
1	850-960	GSM /CDMA	0.5W
2	1805-1990	DCS /PCS	0.5W
3	2100-2170	3G / WCDMA / UMTS2100	0.5W
4	2400-2500	2.4G WiFi /Bluetooth	0.5W
5	1520-1620	GPS L1 / Galileo E1 / Glonass L1 / BeiDou B1	0.5W
6	2570~2690MHZ	4G LTE2600	0.5W

● **Technical Parameter**

Items	Specifications
Interception Channel	6 channels
Total Output Power	3W
Regulatory Distance	Radius 5-20m,depends on the signal strength in given area.
Power supply	AC 110~250V to DC 12V
Battery	Built-in,4000mAh
Working Time	about 120mins
Heat Dissipation Method	Built-in Intelligence Cooling System
Weight	Approx.0.8kg
Size	127/250 x 75 x 35mm
Environmental	-20°C to + 55°C operation
Relative humidity	30 ~ 95%

● **Configuration List**

SN	Description	Quantity
1	Handheld Jammer Unit	1 SET
2	Antennas	6 PCS
3	AC charger	1 PC
4	Car charger	1 PC
5	User Manual	1 PC

Notice:

Do not power on if antennas are not connected.

The functional coverage is greatly affected if antennas are not installed correctly. Do ensure the antennas are properly connected before usage.

When power on, keep away from computer, notebook PC, television, audio and AM/FM radio to prevent interference.

The normal operational temperature is about 65 °C. If the temperature is higher than the above, turn off the power immediately and contact local agent for help.

Its functional coverage will depends on the location and strength of the ambient mobile phone base stations.

Placing the device on higher position for better coverage 2 meters height is recommended.

The polymer rechargeable battery has estimated 500 times recharge cycles.

Please contact us local agent to replace battery if it is not rechargeable.

Specification:

Power supply: adapter 50 to 60Hz AC (110-240V AC/12V DC) Car Charger: DC12V IN
Built-in battery:4000mAh, Continue working: Around 120 minutes

Dimensions: (length, width, height) 126x76x35mm (without antenna)

Packing size: 295*260*125mm Net weight: 0.8kg Gross weight: 1.5kg

Total power: 3W;Shielding radius: (2-20) meters at -75dBm Still depends on the strength signal in given area

Warranty: one year from delivery date

Function Introduction:

Each band could be chosen operating or not.

a) Find the dip switch on the side of the device as below left picture.

b 6 arrows toward from OFF to ON (default), by dip switching ON → OFF, each band could be disable.

c) The corresponding LED indicator shall be turn of;



