

ML-M37

Dual Mode Radio(LTE/4G+DMR)

- Support LTE(4G) and DMR Digital Network
- Dual Antenna, Dual Mode and Dual Standby
- 4G Mode for Worldwide Communication
- DMR Mode with Powerful Output 5W
- Dual Work, 4G Mode and DMR/Analog Mode Selective
- Repeater Mode for 4G, and DMR/Analog Communication
- Group Call and individual Call
- REAL PTT Platform for LTE(4G) Version
- With Functional Dispatching System
- GPS Function Optional
- 1.8 Inch Color LCD Display
- Li-ion Battery Capacity 2600mAh
- Emergency Alar, Function
- PC Programmable for Analog
- Superb Clear and Powerful Audio Output



ML-M37

Dual Mode Radio(LTE/4G+DMR)

GENERAL	
Frequency Range	VHF136-174MHz / UHF400-470MHz
Channel Capacity	1024 Channels (16 Channels*64groups)
Operation Voltage	7.4V DC±10%
Battery Capacity	2600mAh/3500mAh Optional
Dimension(W*H*D) (Projections excluded)	53*33*116mm

TRANSMITTER (ETSI EN 300 086 Testing Standard)	
Bandwidth	12.5KHz
RF Power Output(High/Low)	VHF:5W/1W UHF:4W/1W
Modulation(4FSK)	7K60FXD (Data Only); 7K60FXW (Data &Voice)
Spurious Emission	(-) 36dB < 1GHz, (-) 30dB < 1GHz,
Adjacent Channel Power	≥ 65dB
Hum & Noise	≥ 45dB
Audio Response	(+) 1 ~ -3dB(0.3~3KHz)
Digital Response	AMBE +2™
Modulation Distortion	Less than 3%
Frequency Stability	(+/-) 0.5ppm
Digital Protocol	ETSI-TS102 361-1,-2,-3
Modulation Limited	± 2.5@12.5KHz; ±5.0@25KHz

Receiver (ETSI EN 300 086 Testing Standard)	
Sensitivity (12dB SINAD)	Analog: 5% BER: 0.20 V Digital: 5% BER: 0.25 V
Adjacent Channel Selectivity	≥55dB
Intermodulation	≥55dB
Spurious Response Rejection	≥55dB
Audio Response	(+)1~-3dB(0.3~3KHz)
Hum & Noise	≥40dB
Audio Distortion	≤3%
Audio Output	750mW with less than 5% distortion

PoC Part	
Frequency Range	LTE_FDD: B1/B3/B7/B8/B20 WCDMA: B1/B8 GSM: B3/B8 Other Bands Customized
Operation System	Linux
RF Power	≤30dBm / LTE ≤ -96dBm
Working Temperature	-20 ~ +60 °C
GPS	Optional