



TSVL-8 STALINGRAD

Modular, long-range sniper rifle for all-around use

Caliber - 338 LAPUA MAGNUM

STANDARD PACKAGE:

- Trigger pull – 50-1500 g
- Bolt handle – right
- Bolt action – right
- Magazine – 5 rounds
- Muzzle brake – T-tuner (3-port)
- Precision – 0,4 MOA / 12 mm distance between the centers (5-shot at 100 m)
- Maximum range – 1600 m
- Muzzle velocity – 900 m/s
- Operating temperature range – (-45/+65 C)

PERFORMANCE CHARACTERISTICS:

- Caliber – .338 Lapua Magnum
- Length – 1290 mm (1045 mm folded)
- Height – 190 mm
- Width – 55 mm Weight – 7230 g
- Barrel length – 680 mm



DXL-4M SEVASTOPOL
Ultra long range sniper rifle
Caliber - .408 CheyTac \ .375 CheyTac

STANDARD PACKAGE:

- Trigger pull – 500-1500 g
- Bolt handle – right
- Bolt action – right
- Magazine – 5 rounds
- Scope mount – STD Picatinny rail
- Muzzle brake – T-tuner (4-port)
- Precision – 0,45 MOA / 13,5 mm distance between the centers (5-shot at 100 m)
- Maximum range – 2300+ (.408 Chey Tac) 2800+ m (.375Chey Tac)
- Muzzle velocity – 900+ m/s
- Operating temperature range – (-45/+65 C)

PERFORMANCE CHARACTERISTICS:

- Caliber – .408 Chey Tac\ .375Chey Tac
- Length – 1400 mm (1128 mm folded)
- Height – 210 mm Width (w/o bolt) – 68 mm
- Weight – 8700 g
- Barrel length – 780 mm/ 820 mm /900 mm



DXL-3 LONGSTRIKE

Long range sniper rifle

Caliber - .338 LAPUA MAGNUM

STANDARD PACKAGE:

- Trigger pull – 50-1500 g
- Bolt handle – right
- Bolt action – right
- Magazine – 5 rounds
- Scope mount – STD Picatinny rail
- Muzzle brake – T-tuner (3-port)
- Precision – 0,35 MOA / 10,5 mm distance between the centers (5-shot at 100 m)
- Maximum range – 1800 m
- Muzzle velocity – 900+ m/s
- Operating temperature range – (-45/+65 C)

PERFORMANCE CHARACTERISTICS:

- Caliber – .338 Lapua Magnum
- Length – 1290 mm (1115 mm folded)
- Height – 190 mm
- Width – 60 mm
- Weight – 7950 g
- Barrel length – 740 / 780 / 820 mm



DVL-10 M1 SABOTEUR
Modular, integrated suppressor,
for covert & reconnaissance missions
Caliber - . 338 Federal (8,6 x 51)

STANDARD PACKAGE:

- Trigger pull – 50-500 g
- Bolt handle – right
- Bolt action – right
- Magazine – 5 and 10 rounds
- Scope mount – STD Picatinny rail
- Suppressor – LISS 2.0 TI
- Precision – 0,5 MOA / 15 mm distance between the centers (5-shot at 100 m)
- Maximum range – 400 m (subsonic .338 Fed) 800 m (supersonic .338 Fed and .308 Win)
- Muzzle velocity – 300 m/s (subsonic), 800 m/s (supersonic)
- Operating temperature range – (-45/+65 C)

PERFORMANCE CHARACTERISTICS:

- Caliber – .338 Federal (8,6 x 51)
- Length – 1060 mm (825 mm folded)
- Height – 180 mm
- Width – 55 mm
- Weight – 5700 g
- Barrel length – 500 mm



DVL-10 M2 URBANA
Modular, integrated suppressor,
for covert & reconnaissance missions
Caliber - .308 Win / 6,5-47 Lapua

STANDARD PACKAGE:

- Trigger pull 50-1500 g
- Bolt handle – right
- Bolt action – right
- Magazine – 5 and 10 rounds
- Scope mount – STD Picatinny rail
- Muzzle brake – T-Tuner (2-port)
- Precision – 0,38 MOA / 11,5 mm distance between the centers (5-shot at 100 m)
- Maximum range –900 m (for .308 Win), 1100 m (for 6,5-47 Lapua)
- Muzzle velocity – 840 m/s
- Operating temperature range – (-45/+65 C)

PERFORMANCE CHARACTERISTICS:

- Caliber – .308 Win / 6,5-47 Lapua
- Length – 1223 mm (990 mm folded) (990 mm folded)
- Width – 55 mm
- Weight – 6000 g
- Barrel length – 660 mm



SVLK-14 S TWILIGHT
Extreme long-range target rifle
Caliber - 408 CheyTac \ .338LM \ .300WM

STANDARD PACKAGE:

- Trigger pull – 500-1500 g
- Bolt handle – right
- Bolt action – right
- Muzzle brake – multi-port
- Precision – 0,3 MOA / 9 mm distance between the centers (5-shot at 100 m)
- Maximum range – 2500+ m(.408 Chey Tac) 3000+ m. (375Chey Tac) (WR 4210 m)
- Muzzle velocity – 900+ m/s
- Operating temperature range –(-45/+65 C)

PERFORMANCE CHARACTERISTICS:

- Caliber – .408 Chey Tac\375Chey Tac
- Length – 1430 mm
- Height – 175 mm
- Width (w/o bolt) – 96 mm
- Weight – 9600 g
- Barrel length – 900 mm