



MILKOR
AIR | LAND | SEA | CYBER

**WEAPON
SYSTEMS**



	SuperSix MRGL	Stopper Convertable	UBGL	Mk 1S/L	MAR
Caliber & Rounds	40 mm Less Lethal, Standard Low and Medium Velocity Ammunition	Less Lethal, 37, 38 and 40 mm Low Velocity Ammunition, Light weight	Standard 40mm Low Velocity Ammunition, Extremely Light weight	Less Lethal, Standard 40mm Low Velocity Ammunition	37, 38 and 40 mm Anti-Riot Ammunition Only
Type	Multi-shot Semi-Automatic revolving action	Single Round Break-open weapon	Single shot	Multi-shot Semi-Automatic revolving action	Multi-shot Semi-Automatic revolving action
Capacity	6 Rounds	1 Round	1 Round	6 Rounds	6 Rounds
Firing Method	Double Action	Double Action	Single Action -Button Trigger	Double Action	Double Action
Practical Firing Rate	Capable of ring 6 Rounds in 3 seconds (Operator dependant)	Capable of ring 12 Rounds per minute (Operator dependant)	Capable of ring 6 Rounds in a minute (Operator dependant)	Capable of ring 6 Rounds in 3 seconds (Operator dependant)	Capable of ring 6 Rounds in 3 seconds (Operator dependant)
Barrel Type	Progressive with 1 Turn in 1200 mm nal twist (1:47.24")	Progressive with 1 Turn in 1200 mm nal twist (1:47.24")	6 constant (1 turn in 1200 mm) (1:47.24")	Progressive with 1 Turn in 1200 mm nal twist (1:47.24")	Progressive with 1 Turn in 1200 mm nal twist (1:47.24")
Overall length (Butt extended/ retracted)	758 mm / 824mm Without Compensator 781 mm / 860 mm With Compensator	591 mm / 669mm	274 mm	768 mm / 865mm (Mk-1L) 752 mm / 830mm (Mk-1S)	752 mm / 830mm
Weight (empty)	5.96 kg	2.1 kg	1 kg	6.24 kg (Mk-1L) 5.71 kg (Mk-1S)	4.1 kg
Effective Range	375 m Low Velocity Ammunition & 800 m Medium Velocity Ammunition	375 m Low Velocity Ammunition	375 m Low Velocity Ammunition	375 m Low Velocity Ammunition	25 m Anti-Riot Ammunition
Picatinny Rail	Standard MIL-std-1913 Top Mounted Picatinny	Standard MIL-std-1913 Top Mounted Picatinny & 2 Side mounted 44 mm Picatinny Rails	N/a	Standard MIL-std-1913 Top Mounted Picatinny	Standard MIL-std-1913 Top Mounted Picatinny
Standard Sight	Several Options are available as per customer request	Several Options are available as per customer request	N/a	Several Options are available as per customer request	Several Options are available as per customer request
Height	201 mm	165 mm	90 mm	207 mm	207 mm
Width	163 mm	65 mm	60 mm	163 mm	163 mm

