

SCFF-03C Counterpunch 6-25x56 FFP High Profile w/ MP Reticle

FREE 30mm Tactical One Piece Triple Rails Weaver Mount,
Tested on 50 Caliber,
Long Eye Relief,
Honeycomb Filter Sunshade,
First Focal Plane Etched Glass MP Reticle with Germany Tech,
1cm 1/10 MIL Adjustment.
30mm Monotube,
Lens Caps,
Min Focus at 10 Yard,
Green & Red Illumination



Magnification: 6-25x
Objective Lens Dia: 56mm
Ocular Lens Dia: 34mm
Ocular Length: 52mm
Exit Pupil: 2.4-9.2 mm
Length: 395mm (15.55 inch, without sunshade)
Weight (net): 917g (32.35 ounce)
Eye Relief: 84-107 mm (3.34-4.21 Inch), long eye relief
Field of View (ft@100yds): 4.9-18.6
Field of View (M@ 100M): 1.5-5.7
Field of View (@100yds):0.93-3.55°
Num of Lens: 12
Optics Coating: Fully-Multi Coated to eliminate glare and maximize light transmission
Parallax: ± 0.125
Side Focus Range: 10 Yard to unlimited
Reticle: Front Focal Plan Etched MP Glass Reticle
Elevation Range: 21 MIL
Windage Range: 21 MIL
5 levels green and red brightness illumination system
30mm Hammer-forged Monotube
Shock proof (1000g), water proof (at 300mm and 54 degree) and fog proof (Nitrogen Purged)
High quality aluminum alloy in durable black matte finish
Feature 1/10 MIL (1cm or called 0.1 MARD) direct high finger diamond style windage and elevation turrets adjustments
Fast focus eyepiece at ocular lens adjustment (diopter compensation)
Free fittings involved: 30mm tactical one piece triple rails picatinny mount (as picture shown), lens cap, honeycomb sunshade and fine package