

Eco-Friendly 40mm Low Velocity Practice Grenades



40mm Low Velocity CTS-40 Practice Grenade

Safety : centrifugal type of safety device and low rate of flying fragments provide good safety during 40mm training

No Fire at target area from explosion

Very low misfire rate: nearly 0% misfire rate even on mud, water, grass, etc

Environmentally friendly materials are used such as naturally degraded clay filler and bio degradable plastic ogive

Good sound & smoke effect : Upon impact with the target, high level of sound and yellow smoke puff simulate explosive real-life impact



COMPLETE ROUND

Type: Practice (Smoke)

Weight: 215g

Length: 100mm

Diameter: 40mm

PROJECTILE

Material: Aluminum Skirt, PLA ogive

Filler : Sound and Yellow smoke charge

Color: Blue with white marking

Safety device: centrifugal type

CASE COMPONENTS

Cartridge Case: CN40

Propellant: M9, 380mg

Primer: Percussion

TEMPERATURE LIMITS

Firing Temp range: -30°C~50°C

Storage Temp Range: -30°C~60°C

PERFORMANCE

Maximum range: 400m

Muzzle velocity: 76mps

Sound level: 100dB at 50m

Smoke: Yellow, visible at 200m

WEAPONS IN USE

M203, M79, H&K69, K201 and other compatible NATO qualified low velocity 40mm grenade launchers

PACKING DATA

36 rounds / Barrier bag

2 barrier bags / Wooden box

STORAGE AND SHIPPING DATA

UN serial number: 0330

Hazard class : 1.4C

40mm Low Velocity CTD-40 Practice Grenade

Environmentally friendly materials are used such as naturally degraded clay filler and bio degradable plastic ogive

Economically smart training by cheap price

Safety : Low rate of flying fragments provide good safety during 40mm training

No Fire at target area by explosion

Low misfire rate

Smoke effect: Upon impact with the target, a puff of ivory smoke simulates real-life explosion



COMPLETE ROUND

Type: Practice

Weight: 215g

Length: 100mm

Diameter: 40mm

PROJECTILE

Material: Aluminum Skirt, PLA ogive

Filler : Ivory dye with clay compound

Color: Blue with white marking

Safety device: None

CASE COMPONENTS

Cartridge Case: CN40

Propellant: M9, 380mg

Primer: Percussion

TEMPERATURE LIMITS

Firing Temp range: -30°C~50°C

Storage Temp Range: -30°C~60°C

PERFORMANCE

Maximum range: 400m

Muzzle velocity: 76mps

Sound level: None

Smoke: Ivory, visible at 200m

WEAPONS IN USE

M203, M79, H&K69, K201 and other compatible NATO qualified low velocity 40mm grenade launchers

PACKING DATA

36 rounds / Barrier bag

2 barrier bags / Wooden box

STORAGE AND SHIPPING DATA

UN serial number: 0330

Hazard class : 1.4C

40mm Low Velocity CTM-40 Practice Grenade

Safety : centrifugal type of safety device and low rate of flying fragments provide good safety during 40mm training

No Fire at target area from explosion

Very low misfire rate: nearly 0% misfire rate even on mud, water, grass, etc

Good sound & smoke effect : Upon impact with the target, high visible orange smoke emit around 20~25 sec.



COMPLETE ROUND

Type: Smoke Target Marker

Weight: 227g

Length: 103mm

Diameter: 40mm

PROJECTILE

Material: Aluminum Skirt, PC ogive

Filler : Smoke composition

Color: Yellow with Black marking

Safety device: Centrifugal

CASE COMPONENTS

Cartridge Case: CN40

Propellant: M9, 380mg

Primer: Percussion

TEMPERATURE LIMITS

Firing Temp range: -30°C~50°C

Storage Temp Range: -30°C~60°C

PERFORMANCE

Maximum range: 400m

Muzzle velocity: 76mps

Sound level: None

Smoke: Orange smoke 20 sec.

WEAPONS IN USE

M203, M79, H&K69, K201 and other compatible NATO qualified low velocity 40mm grenade launchers

PACKING DATA

36 rounds / Barrier bag

2 barrier bags / Wooden box

STORAGE AND SHIPPING DATA

UN serial number: 0330

Hazard class : 1.4C

